

# Technical Details



| 35 to 50 millimeters<br>09-0414 |      |       |                 |
|---------------------------------|------|-------|-----------------|
| Measuring Range                 |      | Anvil | Washer          |
| 35.0                            | 35.5 | 35    |                 |
| 35.5                            | 36.0 | 35    | 0.5             |
| 36.0                            | 36.5 | 35    | 1.0             |
| 36.5                            | 37.0 | 35    | 0.5 + 1.0       |
| 37.0                            | 37.5 | 35    | 2.0             |
| 37.5                            | 38.0 | 35    | 2.0 + 0.5       |
| 38.0                            | 38.5 | 35    | 3.0             |
| 38.5                            | 39.0 | 35    | 3.0 + 0.5       |
| 39.0                            | 39.5 | 35    | 3.0 + 1.0       |
| 39.5                            | 40.0 | 35    | 3.0 + 1.0 + 0.5 |
| 40.0                            | 40.5 | 40    |                 |
| 40.5                            | 41.0 | 40    | 0.5             |
| 41.0                            | 41.5 | 40    | 1.0             |
| 41.5                            | 42.0 | 40    | 0.5 + 1.0       |
| 42.0                            | 42.5 | 40    | 2.0             |
| 42.5                            | 43.0 | 40    | 2.0 + 0.5       |
| 43.0                            | 43.5 | 40    | 3.0             |
| 43.5                            | 44.0 | 40    | 3.0 + 0.5       |
| 44.0                            | 44.5 | 40    | 3.0 + 1.0       |
| 44.5                            | 45.0 | 40    | 3.0 + 1.0 + 0.5 |

| 35 to 50 millimeters<br>09-0414 |      |       |                 |
|---------------------------------|------|-------|-----------------|
| Measuring Range                 |      | Anvil | Washer          |
| 45.0                            | 45.5 | 45    |                 |
| 45.5                            | 46.0 | 45    | 0.5             |
| 46.0                            | 46.5 | 45    | 1.0             |
| 46.5                            | 47.0 | 45    | 0.5 + 1.0       |
| 47.0                            | 47.5 | 45    | 2.0             |
| 47.5                            | 48.0 | 45    | 2.0 + 0.5       |
| 48.0                            | 48.5 | 45    | 3.0             |
| 48.5                            | 49.0 | 45    | 3.0 + 0.5       |
| 49.0                            | 49.5 | 45    | 3.0 + 1.0       |
| 49.5                            | 50.0 | 45    | 3.0 + 1.0 + 0.5 |
| 50.0                            | 50.5 | 50    |                 |
| 50.5                            | 51.0 | 50    | 0.5             |
| 51.0                            | 51.5 | 50    | 1.0             |
| 51.5                            | 52.0 | 50    | 0.5 + 1.0       |
| 52.0                            | 52.5 | 50    | 2.0             |
| 52.5                            | 53.0 | 50    | 2.0 + 0.5       |
| 53.0                            | 53.5 | 50    | 3.0             |
| 53.5                            | 54.0 | 50    | 3.0 + 0.5       |
| 54.0                            | 54.5 | 50    | 3.0 + 1.0       |
| 54.5                            | 55.0 | 50    | 3.0 + 1.0 + 0.5 |

