

Speeds and Feeds



						HCSNP2 - Haas Square Negative Positive 2
Material			Grade	Inserts	Recommended Cutting Speed	Recommended Feed Per Tooth
Group	Description	Hardness (HB)				
P Steel	Unalloyed Steel	< 180	HMP35 HK25	02-0624 02-1123	720 - 1150	0.004 - 0.012
	Low-alloyed Steel	180 - 280	HMP35 HK25	02-0624 02-1123	720 - 1050	0.004 - 0.012
	High-Alloyed Steel and Tool Steel	280 - 350	HMP35 HK25	02-0624 02-1123	590 - 980	0.004 - 0.012
M Stainless Steel	Stainless Steel	< 270	HMP35	02-0624	360 - 880	0.003 - 0.008
K Cast Iron	Grey Cast Iron, Ductile Cast Iron, Malleable Cast Iron	180 - 250	HK25	02-1123	490 - 980	0.004 - 0.012

Speeds and Feeds



Feed Rate, Per Revolution (in/min)
$v_f = f_n \cdot n$

Feed Rate, Per Tooth (in/min)
$v_f = f_z \cdot n \cdot Z$

Feed Per Revolution (in/rev)
$f_n = \frac{v_f}{n}$

Feed Per Tooth (in)
$f_z = \frac{v_f}{n \cdot Z}$

Cutting Speed (ft/min)
$v_c = \frac{\pi \cdot D_{tool} \cdot n}{12}$

Spindle Speed (rev/min)
$n = \frac{v_c \cdot 12}{\pi \cdot D_{tool}}$

Material Removal Rate (in ³ /min)
$MMR = a_p \cdot a_e \cdot v_f$

Inch

Symbol	Definition	Unit
v_f	Feed rate	in/min
f_n	Feed per revolution	in/rev
f_z	Feed per tooth	in
v_c	Cutting speed	ft/min (SFM)
n	Spindle speed	rev/min (RPM)
D_{tool}	Tool cutting diameter	in
MMR	Material removal rate	(in ³ /min)
a_e	Radial depth of cut	in
a_p	Axial depth of cut	in
Z	Number of teeth/flutes	